



## Picture Perfect Wireless Security

# Agility™ 3

Picture Perfect Wireless Security



RISCO Group's Agility 3 elegantly combines state-of-the-art video verification and Smartphone apps with advanced wireless security and safety features.

Monitoring stations can now identify false alarms, as video verification enables immediate confirmation of a crime-in-progress, prioritizing response and increasing efficiency.

For the self-monitoring market, the Smartphone app is ideal, as homeowners want on-the-go control and monitoring of their home security.

Featuring remote management, advanced communication, simple installation, and a comprehensive range of peripherals, Agility 3 with video verification is the ideal wireless solution for residential and small commercial installations.

**Wireless Security... Appgraded**



### eyeWave™ Wireless PIR Camera

- Wireless PIR detector with integrated camera
- PIR coverage 12m wide angle
- VGA/QVGA resolution with 85° field of view
- Discreet IR flash provides imaging in complete darkness, up to 10m range
- Battery save mode while system is disarmed



### Security

- Complete range of wireless indoor, outdoor and perimeter detectors
- Indoor and outdoor wireless sounders



### Outdoor & Perimeter

#### Wireless WatchOUT™

- Reliable outdoor detection with 2 PIR channels, and IP65 rating
- 1-way and 2-way versions available

#### Wireless Beams

- Reliable perimeter detection
- Direct sunlight immunity
- 1-way and 2-way versions available



### Safety

- Smoke, Gas, CO and Flood detectors



### Elderly Care

- Stylish and water-resistant Wristband Panic Transmitter
- Alerts if an elderly parent is immobile in the home over a defined period



### Home Automation

- 2-way wireless Input/Output Expander
- 4 wired inputs and 4 outputs



### 2-way Wireless LCD Keypad

- Integrated proximity reader for arm/disarm
- Adaptive menu displays only the relevant options according to the installation and set up



### New 2-way Wireless Slim LED Keypad

- Full system user operation
- Door chime feature
- Outdoor version available
- Available with Proximity Reader



### 2-way Remote Control

- Multi color LEDs indication for system status
- PIN code for higher security



### New Main Panel - New Features

- Dual Core Wireless provides two simultaneous 2-way wireless channels with separate antennas - one for alarm, control and diagnostic signals, a second for video image transmission
- SIA-IP support provides a protocol for enhanced communication with monitoring stations
- Digital Voice Module for enhanced voice quality
- Multi-lingual support for voice and keypad display





RISCO Cloud Server

GSM/GPRS

IP/Internet

PSTN/Dial Up



Monitoring Station



## Video Verification

RISCO Group's Wireless Video Verification solution verifies alarms with a sequence of snapshots, reducing false alarm costs. When armed, the camera is automatically activated by an event and captures a sequence of images during the alarm, and sends the images to users via RISCO's Smartphone and Web applications. Users can also trigger images on demand via the applications to verify events and determine the most appropriate response in real-time.

## Smartphone App

Homeowners can now enjoy the iRISCO Smartphone App for smart and easy control of their Agility system. The revolutionary app enables users to arm/disarm the system on-the-go, visually verify alarms by viewing images taken by their PIR Cameras, take snapshots, activate home automation devices, bypass detectors, view the system's status and history, and much more. Available for iPhone, iPad and Android.

## Web Application

RISCO Group's interactive Web application enables homeowners to monitor, control and configure their Agility system from any location. In addition to all the capabilities of the Smartphone app, with the Web Application users can also configure RISCO's PIR Camera settings such as the number of images taken, image resolution, and more. The application is powered by the RISCO Cloud server.

## Remote Upgrade & Configuration Software


RISCO's Configuration Software saves installers time and money by enabling simple installation, remote configuration, automatic system diagnostics and remote upgrade of the Agility panel.



Agility 3 offers a complete range of safety, security and home automation accessories, both 1-way and 2-way wireless that can be combined in the same installation.



### Agility 3 Specifications

|                                  |   |
|----------------------------------|---|
| Wireless zones (1-way or 2-way)  | 32  |
| Partitions                       | 3   |
| Wireless Sounders (2-way)        | 3 (Indoor or Outdoor)   |
| Wired Zones                      | 4 (with I/O Expander)   |
| Wired Outputs                    | 4 (with I/O Expander): 2x3A relay and 2x500mA   |
| Wireless PIR Cameras             | 8   |
| Keypads (2-way)                  | 3 - LCD or Slim ( <b>New</b> )  |
| Remote Controls (1-way or 2-way) | 8 (4 button or 8 buttons)   |
| X-10                             | Supported with I/O Expander   |
| User codes                       | 32  |
| Event log                        | 250   |
| Monitoring Station Accounts      | 3   |
| Follow-me destinations           | 16  |
| Communication                    | PSTN, IP, and GSM/GPRS in any combination   |
| Reporting formats                | Contact ID, SIA level 2 & 3 (text support), IP/GSM Receiver, SIA IP (with encryption)   |
| Installer Programming Methods    | Local using RS232 for Configuration Software<br>Local using LCD 2-way keypad<br>Remote using configuration software (GPRS, IP, PSTN)<br><b>New</b> - Listener mode for GPRS programming   |
| Firmware upgrade                 | Local or remote via GPRS or IP  |
| Automated scheduling             | 8 (Arm/Disarm or output control)  |
| End user features                | <ul style="list-style-type: none"> <li><b>New</b> - Smartphone apps and web browser for video verification, Arm/disarm, control and monitoring the system </li> <li>Email: Event and images notification</li> <li>SMS: Event notification and remote control</li> <li>Audio: Voice event messaging, touch-tone control with full voice menu guide, two-way audio for listen-in and speak-in</li> </ul> |
| Dimensions (H x W x D)           | 640 x 268.5 x 219.5 mm (10.57 x 8.64 x 2.52 inch)   |
| Approvals                        | EN50131 Grade 2, Class II; EN50136; INCERT; SBSC  |



**Alarmwise**  
**15 Clarendon Green**  
**Orpington**  
**Kent**  
**BR5 2NY**

**Tel: 01689 836 929**

**Email: sales@alarmwise.co.uk**

**Web: www.alarmwise.co.uk**